



COREtec Originals Enhanced CR501

Product Specifications

Style Number	CR501	
Construction	Waterproof Foamed Core	
Edge Profile	Enhanced Painted Bevel	
Nominal Dimensions	9" wide, 72" long	
	US Units	Metric Units
Actual Product Width	8.98"	23 cm
Actual Product Length	72.05"	183 cm
Wear Layer Thickness	22 mil (0.022")	0.55 mm
Overall Product Thickness	0.314"	8 mm
Core Thickness	0.256"	6.5 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.059"	1.5 mm
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	

Packaging

Area per Box	26.94 sq ft	2.5 sq m
Pieces per Box	6 pcs	
Weight per Box	46.3 lbs	21 kg
Boxes per Pallet	40 boxes	



2079 Saffron Pecan

Colors



COREtec Originals Enhanced CR501

Performance


Static Load (ASTM F970)	Passes
Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Smoke Density (ASTM E662)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.


Warranties

Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof
 USF 10 Year Medium Commercial


Coordinating Trim




Baby Threshold*
 BT7CT | 94"



T-Molding*
 TM7CT | 94"



Quarter Round
 QTRCT | 94"



Flush Stairnose
 FS7HU | 94"

*Packaged with molding track

Stair Tread



Stair Tread
 03Z70 | 48"

NEW JERSEY SHOWROOM

406B West Broadstreet, Westfield NJ, 07090
 908.232.6600
 Joe@Hugginsflooring.com
 Newyorkcitywoodfloors.com